


Overview



1. Menu

Opens, selects or exits the OSD menu.

2. Minus "-"

If the OSD menu is on, press to navigate backward through the OSD menu and decrease adjustment levels.

3. Plus "+" / Input

If the OSD menu is on, press to navigate forward through the OSD menu and increase adjustment levels.
If the OSD menu is inactive, press to activate the source button that chooses the video signal source input (VGA or DVI).

4. OK/Auto

If the OSD menu is on, press to select the highlighted menu item. If the OSD menu is inactive, press to activate the auto adjustment feature to optimize the screen image.

5. Power

Turns the monitor on or off.

6. Power LED

LED:
fully powered = blue ;
sleep mode = amber;
sleep timer mode = flashing amber.

Overview



Use two HP V201 19.45-inch monitors combined with an HP Adjustable Dual Display Stand (AW664AA) for a small footprint, high productivity work solution.

(Multi-monitor support depends on your PC capability. Monitors and stands sold separately)

Model

E6W38AA

Technical Specifications

Panel	Type	TN (Twisted Nematic) LED Backlit LCD
	Viewable Image Area (diagonal)	49,4 cm (19.45 in) widescreen, diagonally measured
	Active Area (W x H)	43,3 x 23,6 cm (17.04 x 9.29 in); ± 3 mm
	Aspect Ratio	16:9
	Viewing Angle (typical)*	Up to 90° horizontal/50° vertical (10:1 minimum contrast ratio)
	Brightness (typical)*	200nits (cd/m ²)
	Static Contrast Ratio (typical)*	600:1
	Dynamic Contrast Ratio (typical)*	3,000,000:1
	Response Rate (typical)*	5 ms (On/Off)
	Pixel Pitch	0.27 mm
	Backlight Lamp Life (to half brightness)*	30,000 hours minimum
	Color Gamut (typical)*	72%
	Color Support **	Can display up to 16.7 million colors
<p>*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.</p>		
<p>** With the use of FRC technology.</p>		
On Screen Display (OSD) Controls	Buttons or Switches	Menu, Minus ("-"), Plus ("+")/Source, OK/Auto, Power
	Languages	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)
	User Controls	Brightness, Contrast, Image Control, OSD control, Languages, Color, Management, Information, Factory Reset, Input Control, Exit
Signal Interface/Performance	Horizontal Frequency	24 to 83 kHz
	Vertical Frequency	50 to 75 Hz
	Native Resolution	1600 x 900 @ 60 Hz
	Preset VESA Graphic Modes (non-interlaced)	1600 x 900 @ 60 Hz 1440 x 900 @ 60 Hz 1280 x 1024 @ 60 Hz 1280 x 720 @ 60 Hz 1024 x 768 @ 60 Hz 800 x 600 @ 60 Hz 720 x 400 @ 70 Hz 640 x 480 @ 60 Hz
	Maximum Pixel Clock Speed	170 MHz
	User Programmable Modes	Yes (10)

Technical Specifications

	Anti-Glare	Yes
	Default Color	6500 K
	Temperature	
Video/Other Inputs	Plug and Play	Yes
	Input Connectors	VGA (analog)
	USB	N/A
	Video Cables	(1)VGA
	Video Cable Lengths	1,8 m (5.9 ft)
	Audio	N/A
Power	Power Supply	Internal
	Input Power	90 - 265 VAC at 45 - 63 Hz
	Typical Power Consumption	18 W
	Maximum	20 W
	Power Saving	0.5 W
Mechanical	Power Cable Length	1,9 m (6.2 ft)
	Dimensions (W x D x H)	Unpacked w/ stand 46,8 x 19 x 35,52 cm (18.44 x 7.49 x 14 in)
		Unpacked w/o stand (head only) 46,8 x 4,69 x 28,82 cm (18.44 x 1.85 x 11.36 in)
		Packaged 53,8 x 12,5 x 42 cm (21.2 x 4.93 x 16.55 in)
		Base area (footprint) 20,5 x 19 cm (8.08 x 7.49 in)
	Weight	Head only 2,5 kg (5.5 lb)
		Unpacked 2,8 kg (6.2 lb)
		Packaged 4,2 kg (9.3 lb)
Environmental	Tilt Range	-5° to + 15° vertical
	Swivel Range	N/A
	Height Adjustable	N/A
	Pivot Rotation	N/A
	Base	Detachable
	Temperature – Operating	5° to 35° C (41° to 95° F)
	Temperature – Non-operating	-20° to 60° C (-4° to 140° F)
	Humidity – Operating	20% to 80% non-condensing
	Humidity – Non-operating	5% to 95%, 38.7° C max wet-bulb
	Altitude – Operating	0 to 5,000 m (16,404 ft)
	Altitude – Non-operating	0 to 12,192 m (0 to 40,000 ft)
	White LED Backlights	Yes

Technical Specifications

CCFL Panel	No
Arsenic-Free Display Glass	Yes
Low Halogen³	No
Mercury- Free Display Backlighting	Yes
Environmental Data	Eco-Label Certifications & declarations This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none">IT ECO declaration
Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz 230VAC, 50Hz 100VAC, 60Hz
Normal Operation	14.6 W
Sleep	0.23 W
Off	0.15 W
Heat Dissipation*	115VAC, 60Hz 230VAC, 50Hz 100VAC, 60Hz
Normal Operation	50 BTU/hr
Sleep	1 BTU/hr
Off	1 BTU/hr
Additional Information	<ul style="list-style-type: none">This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.This product contains 0 % post-consumer recycled plastic (by wt.)This product is 98.4 % recycle-able when properly disposed of at end of life.
Packaging Materials	External: PAPER/Paper 535.6 g Internal: PLASTIC/EPS (Expanded Polystyrene) 259.56g PLASTIC/EPE-Expanded Polyethylene 25.2 g PLASTIC/Other plastics unknown 3 g
RoHS Compliance	Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by

Technical Specifications

meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at: <http://www.hp.com/hpinfo/globalsustainability/environment/pdf/gse.pdf>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management Hewlett-Packard offers end-of-life HP product return and recycling programs

Technical Specifications

	and Recycling	in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.
	Hewlett-Packard Corporate Environmental Information	The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers . These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.
	HP LCD Monitor Quick Release - Part number EM870AA1	For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalsustainability/gcreport/index.html Eco-label certifications http://www.hp.com/hpinfo/globalsustainability/environment/productdesign/ecolabels.html ISO 14001 certificates: http://www.hp.com/hpinfo/globalsustainability/environment/operations/envmanagement.html
Options (sold separately)	HP LCD Monitor Quick Release - Part number EM870AA1	An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.
	HP Business PC Security Lock Kit - Part number PV606AA	Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.
	HP Single Monitor Arm - Part number BT861AA	The flexible design of the HP Single Monitor Arm provides a seemingly endless range of display adjustments with an amazing 13 inches of lift, 50 degrees of tilt, and 360 degrees of pan and rotation - all at your fingertips -- helping you stay comfortable and productive throughout the day.
	HP Adjustable Dual Display Stand - Part Number AW664AA	Premium space-saving dual screen solution provides access to more monitor real estate and makes it possible to manage multiple applications simultaneously. Weight adjustable for dual monitors from 17-24". Rotate displays into portrait/landscape positions.
What's in the box?	Monitor and Accessories	HP V201 19.45-inch LED Backlit Monitor; VGA cable; AC Power cable
	Documentation	Printed documentation and CD
	Featured Software	Yes, HP Display Assistant
	User Guide Languages	English, French, Brazilian Portuguese, Spanish
	Warranty Languages	English, French, Brazilian Portuguese, Spanish
	Color	Black
	VESA External Mounting	Yes (one set of standard 4-hole pattern, 100 mm)
	Security Lock-Ready	Yes
	Country of Origin	China

Technical Specifications

Certification and Compliance	CB, ETL, S-mark, NOM, FCC, ICES
Compatibility	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
Service and Warranty	Protected by HP, including a 3 year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard warranties. ²

© Copyright 2013 Hewlett-Packard Development Company, L.P.

¹The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

²HP Care Pack Services are sold separately. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. See www.hp.com/go/cpc for details.

³External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.