



Technical Specifications

HP EliteDisplay E201 20-inch LED Backlit Monitor



1. Menu	Opens, selects or exits the OSD menu.	4. OK/Auto	If the OSD menu is on, press to select the highlighted menu item. If the OSD menu is inactive, press to activate the auto adjustment feature to optimize the screen image.
2. Minus "-"	If the OSD menu is on, press to navigate backward through the OSD menu and decrease adjustment levels.		
3. Plus "+"/Input	If the OSD menu is on, press to navigate forward through the OSD menu and increase adjustment levels. If the OSD menu is inactive, press to activate the source button that chooses the video signal input (VGA, DVI, or DisplayPort).	5. Power/Power LED	Turns the monitor on or off. LED: fully powered = white; sleep mode = amber; sleep timer mode = flashing amber.

Boost Productivity with Dual Monitor Work Solution



(Multi-monitor support depends on your PC capability. Monitors are sold separately.)

Technical Specifications

Model:

C9V73AA

Head only JOG5AA*

***Note: Head only models may not be available in all regions. Head only models are not TCO certified.**

Panel	Type	TN (Twisted Nematic) LED Backlit LCD
	Viewable Image Area (diagonal)	50,8 cm (20 in) widescreen, diagonally measured
	Active Area (W x H)	44,28 x 24,91 cm (17.43 x 9.81 in)
	Aspect Ratio	16:9
	Viewing Angle (typical)*	Up to 170° horizontal/160° vertical (10:1 minimum contrast ratio)
	Brightness (typical)*	250 nits (cd/m ²)
	Static Contrast Ratio (typical)*	1000:1
	Dynamic Contrast Ratio (typical)*	5,000,000:1
	Response Time (typical)*	5 ms (on/off)
	Pixel Pitch	0.276 mm
	Backlight Lamp Life (to half brightness)*	30,000 hours minimum
	Color Gamut (typical)*	72%
	Color Support**	Can display up to 16.7 million colors
	*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.	
	** With the use of FRC technology.	
On Screen Display (OSD) Controls	Buttons or Switches	Menu, Minus ("‐"), Plus ("+") /Input Control, OK/Auto, Power
	Languages	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)
	User Controls	Brightness, Contrast, Color, Image Control, OSD control, Management, Language, Information, Factory Reset, Input Control
Signal Interface/Performance	Horizontal Frequency	24 to 83 kHz
	Vertical Frequency	50 to 76 Hz
	Native Resolution	1600 x 900 @ 60 Hz
	Preset VESA Graphic Modes (non-interlaced)	1440 x 900 @ 60 Hz 1280 x 1024 @ 60 Hz 1280 x 720 @ 60 Hz 1024 x 768 @ 60 Hz 800 x 600 @ 60 Hz 720 x 400 @ 60 Hz 640 x 480 @ 60 Hz
	Maximum Pixel Clock Speed	170 MHz
	User Programmable Modes	Yes (10)
	Anti-Glare	Yes
	Default Color Temperature	6500 K
	Plug and Play	Yes
	Input Connectors	VGA (analog), DVI-D, DisplayPort (HDCP support on DVI-D and DisplayPort)
Video/Other Inputs	USB	Integrated USB 2.0 hub with (2) Downstream and (1) Upstream ports
	USB Cable	(1)USB cable, 1,8 m (5.9 ft)
	Video Cables	(1)VGA, (1)DisplayPort
	<i>APJ Specific:</i>	
	<i>(1)VGA and (1)DVI-D cables are included. DisplayPort cable is only available in Australia and New Zealand).</i>	
	Video Cable Lengths	VGA, DisplayPort & DVI-D 1,8 m (5.9 ft)

Technical Specifications

Power	Audio	N/A				
	Audio Cable Length	N/A				
	Power Supply	Internal				
	Input Power	90 - 265 VAC at 45 - 63 Hz				
	Typical Power Consumption	22 W				
	Maximum	30 W				
	Power Saving	0.5 W				
Mechanical	Power Cable Length	1,9 m (6.2 ft)				
	Dimensions (W x D x H)	Unpacked w/stand	47,28 x 22,89 x 43,48 cm (18.63 x 9.02 x 17.13 in)			
		Unpacked w/o stand (head only)	47,28 x 5,1 x 28,9 cm (18.63 x 2.01 x 11.39 in)			
		Packaged	53,5 x 18,3 x 47,2 cm (21.08 x 7.2 x 18.6 in)			
	Weight	Base area (footprint)	16,69 x 22,89 cm (6.57 x 9 in)			
		Head Only	3 kg (6.6 lb)			
		Unpacked	5,2 kg (11.44 lb)			
Environmental	Adjustments	Packaged	7,1 kg (15.62 lb)			
		Tilt Range	-5° to +30°			
		Swivel Range	Yes, 360°			
		Height Adjustable	Yes, 150 mm			
		Pivot Rotation	Yes, 90°			
		Base	Detachable			
	Temperature	Temperature - Operating	5° to 35° C (41° to 95° F)			
		Temperature - Non-operating	-20° to 60° C (-4° to 140° F)			
		Humidity - Operating	20% to 80% non-condensing			
Environmental Data	Humidity	Humidity - Non-operating	5% to 95%, 38.7° C max wet-bulb			
		Altitude - Operating	0 to 5,000 m (16,404 ft)			
		Altitude - Non-operating	0 to 12,192 m (0 to 40,000 ft)			
	Backlights	White LED Backlights	Yes			
		CCFL Panel	No			
		Arsenic-Free Display Glass⁴	Yes			
	Chemicals	Low Halogen⁵	Yes			
		Mercury- Free Display	Yes			
		Backlighting	Yes			
Environmental Data	Eco-Label Certifications & declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:				
		<ul style="list-style-type: none"> IT ECO declaration US ENERGY STAR® TCO 06 EPEAT® Gold where HP registers commercial display products. See http://www.epeat.net for registration status in your country US Federal Energy Management Program (FEMP) 				
Energy Consumption	(in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz		
	Normal Operation	15.35 W	15.29 W	15.53 W		
	Sleep	0.25 W	0.28 W	0.23 W		
	Off	0.17 W	0.22 W	0.17 W		

Technical Specifications

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation	52 BTU/hr	53 BTU/hr	53 BTU/hr
Sleep	1 BTU/hr	1 BTU/hr	1 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr
*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.			
Additional Information	<ul style="list-style-type: none">• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).• This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net• Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.• This product contains 14.9 % post-consumer recycled plastic (by wt.)• This product is 97.7 % recycle-able when properly disposed of at end of life.		
Packaging Materials	External: PAPER/Cardboard & misc	700 g	
RoHS Compliance	Internal: PLASTIC/EPS (Expanded Polystyrene)	300 g	
	PLASTIC/Polyethylene low density	22 g	
Material Usage	<p>Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).</p> <p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):</p> <ul style="list-style-type: none">• Asbestos• Certain Azo Colorants• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics• Cadmium• Chlorinated Hydrocarbons• Chlorinated Paraffins• Formaldehyde• Halogenated Diphenyl Methanes• Lead carbonates and sulfates• Lead and Lead compounds• Mercuric Oxide Batteries• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.		

Technical Specifications

- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/qcreport/index.html>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

Technical Specifications

Options (sold separately)	HP LCD Monitor Quick Release – Part number EM870AAⁱ	An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.
	HP USB Graphics Adapter – Part number NL571AA	Enables connection of up to six simultaneous displays to help you boost productivity and multi-task across several open applications. Use one Adapter to bridge between a notebook or desktop PC and second monitor or use multiple Adapters to connect several displays to each other.
	HP Business PC Security Lock Kit – Part number PV606AA	Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.
	HP LCD Speaker Bar – Part number NQ576AA	Powered directly by the connected PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and dual external headphone jacks. Sold separately. For more information, refer to the product's QuickSpecs.
	HP Integrated Work Center 2 – Small Form Factor (SFF) – Part number QP897AA	Designed specifically for use with the HP Compaq Small Form Factor (SFF) Desktop PC and a 17 to 24-inch (43.18 to 60.96 cm) diagonal monitor, the HP Integrated Work Center 2 (IWC) - Small Form Factor (SFF) provides a portable, compact workspace to help maximize space-constrained work environments. (17 to 24-inch diagonal monitors need to meet supported weight limits of 7.5 to 12.1 lbs. (3.38 to 5.5 kg). For more information, refer to the product's QuickSpecs.
	HP Adjustable Dual Display Stand – Part Number AW664AA	Premium space-saving dual screen solution provides access to more monitor real estate and makes it possible to manage multiple applications simultaneously. Weight adjustable for dual monitors from 17-24". Rotate displays into portrait/landscape positions.
	HP DVI to DVI Cable – Part number DC198A	Connect to external monitors with a DVI connector from an HP Compaq Business Desktop computer with a DVI connector. The cable is a single link cable with DVI-D support on both connectors. The cable will connect to either a DVI-D or DVI-I connector on the monitor and the graphics card.
What's in the box?	Monitor and Accessories	HP EliteDisplay E201 20-inch LED Backlit Monitor; VGA cable; DisplayPort cable; USB cable; AC Power cable
	Documentation	<i>APJ Specific:</i> (1)VGA and (1)DVI-D cables are included. DisplayPort cable is only available in Australia and New Zealand).
Other	Featured Software User Guide Languages	Printed documentation and CD Yes, HP Display Assistant English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	Warranty Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	Color	Black
	VESA External Mounting	Yes (one set of standard 4-hole pattern, 100 mm)
	Security Lock-Ready	Yes

Technical Specifications

Country of Origin	China
Certification and Compliance	CE, CB, KC, KCC, NOM, PSB, ICE, TUV-S, CCC, CEL Grade 1, CECP, SEPA, TCO Certified Edge, EPA, ISC, VCCI, FCC, BSMI, ENERGY STAR®, EPEAT® Gold ³
Compatibility	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
Service and Warranty	Protected by HP, including a 3 year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard warranties. ²

© Copyright 2013 Hewlett-Packard Development Company, L.P.

ENERGY STAR® is a US registered mark of the United States Environmental Protection Agency.

¹ The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

² HP Care Pack Services extend service contracts beyond the standard warranties. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at <http://www.hp.com/go/lookuptool>. Additional HP Care Pack Services information by product is available at <http://www.hp.com/hps/carepack>.

³ EPEAT® Gold registered models of this product are available where HP registers commercial display products. See www.epeat.net for registration status in your country.

⁴ Arsenic and its compounds were not detected using US EPA Test Methods 3052 & 3052/6010b by ICP or ICP-AES with a Method Detection Limit of 10 ppm.

⁵ External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Technical Specifications

Summary of Changes

Date of change:	Version History:		Description of change:
July 31, 2014	From v1.7 to v7	Added	Added a new model and a disclaimer note
		Added	Added change log
		Upgrade	Change the version, so it would match the PB